

RAMRADE Rock Breaker

The RAMRADE Rock Breakers are designed and built to deliver heavyweight performance and withstand the toughest job sites and extreme conditions. They incorporate excellent hydraulic systems and are proven in quarry, demolition and earthmoving projects around Australia.

KEY FEATURES

- Size range to suit 1.5 - 12 tonne
- Designed for extreme conditions
- Noise reduction technology
- Optional auto-greaser available
- Fully shock absorbed



Unit		100 SERIES	200 SERIES	300 SERIES	400 SERIES	430 SERIES	450 SERIES
Pick-Up Dimensions	mm	85-95-30	85-95-30	180-145-40	245-170-45	300-200-50	375-270-65
Carrier	tonne	0.5 - 1.5	1.2 - 4.0	3.0 - 5.0	3.5 - 7	5-9	7-12
Weight	kg	100	200	250	380	500	650
Chisel Diameter	mm	40	45	53	68	75	85
Required Oil Flow Range	LPM	13 - 25	20 - 30	25 - 40	30 - 45	40 - 80	45 - 85
Setting Pressure	Bar	90 - 130	150	150	170	170	195
Operating Pressure	Bar	75 - 100	80 - 110	90 - 120	95 - 130	100 - 130	130 - 150
Impact Range	BPM	800 - 1200	600 - 1000	550 - 950	500 - 900	450 - 950	400 - 800
Total Impact Range	Joule	157	245	343	735	883	1373